


KEMET Part Number: T242B106K035RS
(M39003/03-0366, CSR23F106KR)

Capacitor, Tantalum, 10 uF, +/-10% Tol, 35 V



Dimensions (mm)		
Symbol	Dimension	Tolerance
D	4.7	+/-0.25
L	12.04	+/-0.79
L2	15.49	
F	0.51	+/-0.05
LL	38.1	+/-6.35
G	3.45	+0.79

Notes:

- Dimensions Include Insulating Sleeve (Standard)
- Lead Length Shown Is For Parts Supplied With Bulk Packaging, When Supplied On T&R Or Ammo, Lead Length Is Determined By Taping Specification
- Failure Rates M ,P, R, And S Are Obsolete For New Designs As Of 1982. MIL-PRF-39003 Suggests B Failure Rate As Replacement.

General Information	
Supplier:	KEMET
Application:	Military ER/General Purpose
Sub Application:	ExtendedRange
Body Type:	Axial Hermetic
Lead Type:	Un-insulated Wire
Termination Type:	Tin-Lead (SnPb)
RoHS:	No

Specifications	
Capacitance:	10 uF
Tolerance:	+/-10%
Voltage:	35 VDC (85C)
Voltage:	28 VDC (125C Surge)
Voltage:	0.35 V (125C Reverse)
Temperature Range:	-55/+125C
Current/Ripple Current:	224 mAmps (100kHz)
Resistance/ESR:	2 Ohms (100kHz)
Failure Rate:	R (0.01%/1000 Hrs)
Testing:	Standard Testing To MIL-PRF-39003
Leakage Current:	3 uA
Dissipation Factor:	4%

Packaging Specifications	
Package Kind:	Bulk
Package Type:	Box
Package Quantity:	75