

## High Value Multilayer Ceramic Capacitors (High dielectric type)

### JMK316BJ106MD-T



#### ■ Features

- Item Summary  
10uF±20%, 6.3V,  
X5R/B, 1206/3216 (EIA/JIS)
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping paper 4000pcs

#### ■ Products characteristics table

Capacitance	10 uF ± 20 %
Case Size (EIA/JIS)	1206/3216
Rated Voltage	6.3 V
tan δ (max)	10 %
Temperature Characteristic (EIA)	X5R
Operating Temp. Range (EIA)	-55 to +85 °C
Temperature Characteristic (JIS)	B
Operating Temp. Range (JIS)	-25 to +85 °C
High Temperature Loading (% Rated Voltage)	200 %
Insulation Resistance (min)	100 MΩ · μF
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Halogen Free	Yes
Soldering	Reflow

#### ■ External Dimensions

Dimension L	3.2 ± 0.15 mm
Dimension W	1.6 ± 0.15 mm
Dimension T	0.85 ± 0.10 mm
Dimension e	0.50 +0.35/-0.25 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.

# Multi Layer Ceramic Capacitor **TAIYO YUDEN**






-Electrical Characteristics Data-

16R3A03

RoHS compliance product

## ○JMK316BJ106MD

**6.3V 3216 B/X5R 10uF +/- 20% t=0.95mmMAX**  
**6.3V 1206 B/X5R 10uF +/- 20% t=0.037inchMAX**



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご利用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the data at any time without notice.

Before making final selection, please check product specification.