



**Single Switch
MOSFET Power Module**

V_{DSS} = 1200V
R_{DSon} = 95mΩ typ @ T_j = 25°C
I_D = 103A @ T_c = 25°C


Application

- Welding converters
- Switched Mode Power Supplies
- Uninterruptible Power Supplies
- Motor control

Features

- Power MOS 7[®] FREDFETs
 - Low R_{DSon}
 - Low input and Miller capacitance
 - Low gate charge
 - Fast intrinsic reverse diode
 - Avalanche energy rated
 - Very rugged
- Kelvin source for easy drive
- Very low stray inductance
 - Symmetrical design
 - M5 power connectors
- High level of integration
- AlN substrate for improved thermal performance

Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Low profile
- RoHS Compliant

Absolute maximum ratings

Symbol	Parameter		Max ratings	Unit
V _{DSS}	Drain - Source Breakdown Voltage		1200	V
I _D	Continuous Drain Current	T _c = 25°C	103	A
		T _c = 80°C	77	
I _{DM}	Pulsed Drain current		412	
V _{GS}	Gate - Source Voltage		±30	V
R _{DSon}	Drain - Source ON Resistance		114	mΩ
P _D	Maximum Power Dissipation	T _c = 25°C	2272	W
I _{AR}	Avalanche current (repetitive and non repetitive)		25	A
E _{AR}	Repetitive Avalanche Energy		50	mJ
E _{AS}	Single Pulse Avalanche Energy		3000	

 **CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handing Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0\text{V}$, $V_{DS} = 1200\text{V}$	$T_j = 25^\circ\text{C}$			0.6	mA
		$V_{GS} = 0\text{V}$, $V_{DS} = 1000\text{V}$	$T_j = 125^\circ\text{C}$			3	
$R_{DS(on)}$	Drain – Source on Resistance	$V_{GS} = 10\text{V}$, $I_D = 51.5\text{A}$			95	114	$\text{m}\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}$, $I_D = 15\text{mA}$		3		5	V
I_{GSS}	Gate – Source Leakage Current	$V_{GS} = \pm 30\text{ V}$, $V_{DS} = 0\text{V}$				± 500	nA

Dynamic Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0\text{V}$ $V_{DS} = 25\text{V}$ $f = 1\text{MHz}$			30.9		nF
C_{oss}	Output Capacitance				4.6		
C_{rss}	Reverse Transfer Capacitance				0.78		
Q_g	Total gate Charge	$V_{GS} = 10\text{V}$ $V_{Bus} = 600\text{V}$ $I_D = 103\text{A}$			1122		nC
Q_{gs}	Gate – Source Charge				144		
Q_{gd}	Gate – Drain Charge				720		
$T_{d(on)}$	Turn-on Delay Time		Inductive switching @ 125°C		20		ns
T_r	Rise Time	$V_{GS} = 15\text{V}$			15		
$T_{d(off)}$	Turn-off Delay Time	$V_{Bus} = 800\text{V}$			160		
T_f	Fall Time	$I_D = 103\text{A}$			45		
E_{on}	Turn-on Switching Energy	Inductive switching @ 25°C $V_{GS} = 15\text{V}$, $V_{Bus} = 800\text{V}$ $I_D = 103\text{A}$, $R_G = 0.8\Omega$			5.9		mJ
E_{off}	Turn-off Switching Energy				4.1		
E_{on}	Turn-on Switching Energy		Inductive switching @ 125°C		9.4		mJ
E_{off}	Turn-off Switching Energy	$V_{GS} = 15\text{V}$, $V_{Bus} = 800\text{V}$ $I_D = 103\text{A}$, $R_G = 0.8\Omega$			5.14		

Source - Drain diode ratings and characteristics


Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit	
I_S	Continuous Source current (Body diode)		$T_c = 25^\circ\text{C}$			103	A	
			$T_c = 80^\circ\text{C}$			77		
V_{SD}	Diode Forward Voltage	$V_{GS} = 0\text{V}$, $I_S = - 103\text{A}$				1.3	V	
dv/dt	Peak Diode Recovery ①					18	V/ns	
t_{rr}	Reverse Recovery Time	$I_S = - 103\text{A}$ $V_R = 600\text{V}$ $dI/dt = 600\text{A}/\mu\text{s}$	$T_j = 25^\circ\text{C}$			320	ns	
			$T_j = 125^\circ\text{C}$			650		
Q_{rr}	Reverse Recovery Charge		$T_j = 25^\circ\text{C}$		12		μC	
			$T_j = 125^\circ\text{C}$		42			






 ① dv/dt numbers reflect the limitations of the circuit rather than the device itself.







 $I_S \leq - 103\text{A}$ $di/dt \leq 700\text{A}/\mu\text{s}$ $V_R \leq V_{DSS}$ $T_j \leq 150^\circ\text{C}$







Thermal and package characteristics
Symbol **Characteristic**

			Min	Typ	Max	Unit
R _{thJC}	Junction to Case Thermal Resistance				0.055	°C/W
V _{ISOL}	RMS Isolation Voltage, any terminal to case t = 1 min, I isol < 1mA, 50/60Hz	2500				V
T _J	Operating junction temperature range	-40		150		
T _{STG}	Storage Temperature Range	-40		125		°C
T _C	Operating Case Temperature	-40		100		
Torque	Mounting torque	To heatsink M6	3		5	N.m
		For terminals M5	2		3.5	
Wt	Package Weight				280	g

SP6 Package outline (dimensions in mm)

 See application note APT0601 - Mounting Instructions for SP6 Power Modules on www.microsemi.com

Typical Performance Curve






Microsemi reserves the right to change, without notice, the specifications and information contained herein

Microsemi's products are covered by one or more of U.S patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 and foreign patents. U.S and Foreign patents pending. All Rights Reserved.